



CONTROS® DETECT

Version History

© CONTROS Systems & Solutions GmbH

Updates for the **Contros™ DETECT** Software package for all versions

Notes:

- ! Corrected or improved
- !! Very important corrections or improvements.
- Removed item
- + New feature
- # Changes, that might be not compatible with former versions.

Release	Date	Note	Changes
0.53	25.11.08	+	First public release
0.64	05.12.08	!	Data logging corrected
1.00.02	02.03.09	!!	New version under C#, multiple sensor / window design
1.00.04	14.03.09	+	MicroDI adaption included, special version
		+	RTC sync
2.00.00	14.03.09	!!	New design, multiple windows
2.00.05	27.03.09	+	Automatic detection of HydroC™ sensors and MicroDI™ Datalogger
		!	Possibility of changing sensors during program operation, e.g. for maintenance
		+	Configure HydroC™ pumping system
		+	Change Names and units of all parameters and channels
		+	Mathematical formula parser to produce new virtual channels and calibration formulas
		+	Virtual channels for each connected device
		+	HydroC™ PAH fluorometer interface
2.00.07	05.05.09	+	Edinburgh Sensor Interface
		+	Native GPS NMEA-0183 interface
		!	Improved menu structure
		!	Some minor errors removed
2.01.09	15.05.09	!! #	New configuration format *.XOS
		+	Option to start without auto-detection and add manually sensors
		! #	Updated software data protocol for MicroDI and HydroC NMEA protocol
2.01.10	15.07.09	#	Change min. baudrate from 9600bps to 19200bps